

TEST & MEASUREMENT



310 Series Residential Meters

- Voltage
- Current
- Resistance
- Audible continuity
- Temperature
- Data hold
- Diode test
- Large numbers displayed
- 2-year warranty



Description	Cat. No.
Resi-Pro™ Meter w/Auto Ranging, AC/DC Current, Capacitance, Frequency, Auto Power Off, Low Battery Indication	61-312
Resi-Pro™ Meter w/Manual Ranging, Tests Batteries	61-310

Includes: Test Leads and Thermocouple.

Specifications	Range & Resolution		Accuracy	
	61-310		61-312	
AC Voltage	200.0/600 V		1.2%	
DC Voltage	200.0m/2.000/20.00/200.0/600 V		0.5%	
Current	200.0m/10.00 ADC		1.5%	
Resistance	200.0/2.000k/20.00k/200.0k/20.00M Ω		1.0%	
Capacitance	—		—	
Frequency	—		—	
Temperature	-4-1382°F (-20-750°C)		2.5%	



Pocket Meter

- Convenient pocket size
- Built-in test stand
- Audible continuity
- Auto power off
- Test lead storage
- 2-year warranty



Description	Cat. No.
Pocket Meter	61-605

Includes: Test Leads.

Specifications	Range & Resolution		Accuracy	
	61-605			
AC Voltage	200.0m/2.000/20.00/200.0/600 V		4.0%	
DC Voltage	200.0m/2.000/20.00/200.0/600 V		2.0%	
Resistance	200.0/2.000k/20.00k/200.0k/2.000M/20.00M Ω		3.0%	



Analog Meters

- Multi-color analog display with mirrored scale
- High-impact thermoplastic case
- Battery test
- 2-year warranty



61-614

Description	Cat. No.
Analog Multimeter w/Audible Continuity, built-in stand	61-614
Analog Multimeter (pocket-size)	61-610

Includes: Test Leads.

	61-610		61-614	
AC Voltage	10/50/250/500 V	+/- 4.0% Full Scale	10/50/250/1000 V	+/- 4.0% Full Scale
DC Voltage	10/50/250/500 V	+/- 3.0% Full Scale	2.5/10/50/250/1000 V	+/- 3.0% Full Scale
DC Current	500μ/50m/250mA	+/- 3.0% Full Scale	5m/50m/500m/20A	+/- 3.0% Full Scale
Resistance	1 M Ω Full Scale 5 k Ω Mid Scale	+/- 3.0% Arc Length	10k/100k/10M Ω Full Scale 50/500/50k Ω Mid Scale	+/- 3.0% Arc Length
Decibels	-20 to +56 dB	—	-8 to +62 dB	—
Battery Test	1.5, 9.0 VDC	—	1.5, 9.0 VDC	—



61-610

61-614